




FOR PARTS USE ONLY				FEATURES																								
B-WIC		12'-0"		<div>ADVISE</div> <div>VOLTAGE: <input type="checkbox"/> 230 3ø 60HZ <input type="checkbox"/> 460 3ø 60 HZ</div>																								
B-HIC		15'-0"		<div>INTERIOR SLAT COLOR: <input checked="" type="checkbox"/> GRAY</div>																								
<div></div>				<div>GRILLE SLATS: (QTY. -) <input checked="" type="checkbox"/> PERFORATED METAL</div>																								
				<div>FRAME MOUNTS TO: (SEE DETAILS) <input type="checkbox"/> MASONRY <input type="checkbox"/> STEEL</div>																								
				<div>BARREL/IDLER SHROUD: <input checked="" type="checkbox"/> NO</div>																								
				<div>DRIVE MOTOR SHROUD: <input checked="" type="checkbox"/> NO</div>																								
				<div>SIDE COVER MATERIAL: <input checked="" type="checkbox"/> GALVANIZED STEEL</div>																								
				<div>EXTENDED CABLE PACKAGE: <input checked="" type="checkbox"/> NO</div>																								
<div>REVERSING EDGE: (WIRELESS) <input checked="" type="checkbox"/> STD REVERSING EDGE (24B0922NN)</div>				<div>REVERSING DEVICE: <input checked="" type="checkbox"/> STD DUAL PHOTO EYES (INTERIOR & EXTERIOR)</div>																								
<div>PRE-ANNOUNCE TO CLOSE: <input checked="" type="checkbox"/> NO</div>				ACTIVATION DEVICES																								
				(X001) () Loop Detector (only) (55B169F7)																								
				(X002) () Loop Detector, W/ Wire & Sealant (55B169F5)																								
				(X027) () Motion Sensor ASI/F (23A284)																								
				(X080) () Motion Sensor Program Remote ASI/B, Loose (23A285)																								
				(X181) () Radio Control, 1-Channel Receiver (23A0510)																								
				(X182) () Radio Control, 1-Channel Transmitter W/Clip (23A0511)																								
(X184) () Radio Control, 2-Channel Transmitter W/Clip (23A0512)																												
(X100) () Pull Cord, Unheated (24C507F1)																												
(X045) () Single Button Station, Unheated (24B029F1)																												
(X047) () 3-Button Station, Open/Close/E-Stop (24A001)																												
				SPECIAL NOTES																								
				TAG DOOR(S) AS: <div>***ADVISE***</div>																								
<div>DOOR SPEED TABLE</div> <table><tr><td>SIZE</td><td>≤ 250 SQ FT</td><td>> 250 SQ FT</td></tr><tr><td>OPEN</td><td>42 IPS</td><td>20 IPS</td></tr><tr><td>CLOSE</td><td>21 IPS</td><td>20 IPS</td></tr></table>		SIZE	≤ 250 SQ FT	> 250 SQ FT	OPEN	42 IPS	20 IPS	CLOSE	21 IPS	20 IPS	<div>DOOR DIMENSIONS</div> <table><tr><td>FINISHED OPENING WIDTH</td><td>A</td><td>12'-0"</td></tr><tr><td>FINISHED OPENING HEIGHT</td><td>B</td><td>15'-0"</td></tr><tr><td>B + 27"</td><td>C</td><td>17'-3"</td></tr><tr><td>A + 28 1/2"</td><td>D</td><td>14'-4 1/2"</td></tr></table>		FINISHED OPENING WIDTH	A	12'-0"	FINISHED OPENING HEIGHT	B	15'-0"	B + 27"	C	17'-3"	A + 28 1/2"	D	14'-4 1/2"	<div>WINDLOCK SIDE FRAME DETAIL: MASONRY MOUNT</div> <div></div>		<div>WINDLOCK SIDE FRAME DETAIL: STEEL MOUNT</div> <div></div>	
SIZE	≤ 250 SQ FT	> 250 SQ FT																										
OPEN	42 IPS	20 IPS																										
CLOSE	21 IPS	20 IPS																										
FINISHED OPENING WIDTH	A	12'-0"																										
FINISHED OPENING HEIGHT	B	15'-0"																										
B + 27"	C	17'-3"																										
A + 28 1/2"	D	14'-4 1/2"																										
<div>MOTOR DATA 3.25 HP (2.5 KW)</div> <table><tr><td>VOLT/PHASE</td><td>FLA</td></tr><tr><td>460/3</td><td>7.5 AMPS</td></tr><tr><td>230/3</td><td>12.5 AMPS</td></tr></table>		VOLT/PHASE	FLA	460/3	7.5 AMPS	230/3	12.5 AMPS	<div>***** ADVISE *****</div> <div>* DOOR TAG: * OPERATOR LOCATION: RIGHT HAND (SHOWN), LEFT IS OPPOSITE * VOLTAGE: 230 OR 460 VOLTS, 3 PHASE * MOUNTS TO: MASONRY OR STEEL</div>																				
VOLT/PHASE	FLA																											
460/3	7.5 AMPS																											
230/3	12.5 AMPS																											
APPROVALS				APPROVAL DRAWING																								
FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.		ASI JOB NUMBER:		QUANTITY OF DOORS:		TITLE																						
BY _____		CUSTOMER ORDER NUMBER:		DOOR MODEL NO: 109G		ALUMINUM ROLLUP DOOR, RIGHT HAND DRIVE																						
DATE _____		SOLD TO:		DOOR ASSEMBLY NO: 91B0025		GFA OPERATOR, (168"<HIC≤240")																						
		END USER:		ELECTRICAL DRAWING NO:		DRAWN BY																						
						DATE																						
						SHEET 1 OF																						
						DRAWING NO.																						
						REV.																						