



NOTE:  
IF USING A JUNCTION BOX TO BRING POWER TO THE OPERATOR USING THE SUPPLIED HEADER CUTOUT, BOX MUST BE FLUSH WITH THE WALL AND WIRING MUST NOT INTERFERE WITH THE DOOR MOTION.

DOOR DIMENSIONS		
FINISHED OPENING WIDTH	A	6'-0"
FINISHED OPENING HEIGHT	B	8'-0"
A + 6"	C	6'-6"
A + 5"	D	6'-5"
2A + 10"	E	12'-10"
B + 12"	F	9'-0"
A + 1"	G	6'-1"

NOTE:  
IF WIC (DIM. "A") > 4'-6" THERE WILL BE A VERTICAL SEAM ON DOOR PANEL

FEATURES

HEADER & RAIL: ■ STAINLESS STEEL	OPERATION: ■ POWER DOOR – 115V, 1Ø
OPERATOR: ■ STANDARD DUTY	SHROUD: ■ SLOPED STAINLESS STEEL
DOOR PANEL MATERIAL: ■ 304 #4 STAINLESS STEEL	
CAPPING, SIDE FRAMES, SHROUD, WINDOW FRAME, & KICKPLATE MATERIAL (IF CHOSEN): ■ 304 #4 STAINLESS STEEL	
WINDOW TYPE: ■ NONE	GLASS TYPE: ■ NONE
OUTSIDE KICKPLATE: ■ NONE	INSIDE KICKPLATE: ■ NONE
KEYED CANEBOLT LOCK: ■ NONE	ELECTRIC LOCK: ■ NONE
PHOTO EYES: ■ (STD) DUAL SIDEFRAME @ 2" & 24"	INTERLOCKING: ■ NONE
BATTERY BACKUP: ■ NO	

ACTIVATION DEVICES

(X042)	( )	Wall Mount, Push Plate, 2-Gang, Loose (23A227)
(PIP1)	( )	Push Plate Kit, In-Panel, 2-Gang (55B0033F07)
(X050)	( )	Touchless Switch, 1 or 2 Gang Mount, Loose (23A288)
(PIP4)	( )	Touchless Plate Kit, In-Panel, 2-Gang (55B0033F04)
(X125)	( )	Touchless Switch, MS11, Single Gang, Loose (23A0488)

SPECIAL NOTES

TAG DOOR AS: **\*\*\*ADVISE\*\*\***

\*\*\*\*\* ADVISE \*\*\*\*\*

- \* DOOR TAG:
- \* SLIDE DIRECTION: RIGHT HAND (SHOWN), LEFT HAND IS OPPOSITE

APPROVAL DRAWING



5848 North 95th Court  
Milwaukee, WI 53225  
1-800-558-7068  
www.asidoors.com

TITLE  
SINGLE SLIDE – POWER DOOR

DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.
----------	------	---------------	-------------	------

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY \_\_\_\_\_ DATE \_\_\_\_\_

ASI JOB NUMBER:  
CUSTOMER ORDER NUMBER:  
SOLD TO:  
END USER:

QUANTITY OF DOORS:  
DOOR MODEL NO: 1250SS  
DOOR ASSEMBLY NO: SGSL  
ELECTRICAL DRAWING NO: 18D248