



DOOR DIMENSIONS		
FINISHED OPENING WIDTH	A	6'-0"
FINISHED OPENING HEIGHT	B	8'-0"
A + 6"	C	6'-6"
A + 5"	D	6'-5"
2A + 10"	E	12'-10"
B + 15"	F	9'-3"

NOTE:
IF USING A JUNCTION BOX TO BRING POWER TO THE OPERATOR USING THE SUPPLIED HEADER CUTOUT, BOX MUST BE FLUSH WITH THE WALL AND WIRING MUST NOT INTERFERE WITH THE DOOR MOTION.

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:
CUSTOMER ORDER NUMBER:
SOLD TO:
END USER:

QUANTITY OF DOORS:
DOOR MODEL NO: 150B
DOOR ASSEMBLY NO: SGSL
ELECTRICAL DRAWING NO: 18D248

FEATURES

HEADER & RAIL: ■ ALUMINUM W/BREAKAWAY	OPERATION: ■ POWER DOOR – 115V, 1Ø
OPERATOR: ■ STANDARD DUTY	SHROUD: ■ SLOPED STAINLESS STEEL
DOOR PANEL MATERIAL: ■ WHITE LAMINATED FIBERGLASS	
CAPPING, SIDE FRAMES, SHROUD, WINDOW FRAME, & KICKPLATE MATERIAL (IF CHOSEN): ■ 304 #4 STAINLESS STEEL	
WINDOW TYPE: ■ NONE	GLASS TYPE: ■ NONE
OUTSIDE KICKPLATE: ■ NONE	INSIDE KICKPLATE: ■ NONE
KEYED CANEBOLT LOCK: ■ NONE	ELECTRIC LOCK: ■ NONE
PHOTO EYES: ■ (STD) DUAL SIDEFRAME @ 2" & 24"	INTERLOCKING: ■ NONE
BATTERY BACKUP: ■ NO	BREAKAWAY PHOTO EYES: ■ (STD) SHROUD MOUNT

ACTIVATION DEVICES

- (X042) () Wall Mount, Push Plate, 2-Gang (23A227)
(PIP1) () Push Plate Kit, In-Panel, 2-Gang (55B0033F07)
(X050) () Touchless Switch, 1 or 2 Gang Mount, Loose (23A288)
(PIP4) () Touchless Plate Kit, In-Panel, 2-Gang (55B0033F04)

SPECIAL NOTES

TAG DOOR AS: *****ADVISE*****

***** ADVISE *****

- * DOOR TAG:
* SLIDE DIRECTION: RIGHT HAND (SHOWN), LEFT HAND IS OPPOSITE

APPROVAL DRAWING



5848 North 95th Court
Milwaukee, WI 53225
1-800-558-7068
www.asidoors.com

TITLE BREAKAWAY SINGLE SLIDE – POWER DOOR				
DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.