



NOTE:
IF USING A JUNCTION BOX TO BRING POWER TO THE
OPERATOR USING THE SUPPLIED HEADER CUTOUT, BOX
MUST BE FLUSH WITH THE WALL AND WIRING MUST NOT
INTERFERE WITH THE DOOR MOTION.

DOOR DIMENSIONS		
FINISHED OPENING WIDTH	A	6'-0"
FINISHED OPENING HEIGHT	B	8'-0"
A/2 + 5"	C	3'-5"
A/2 + 1 1/2"	D	3'-1 1/2"
2A + 10"	E	12'-10"
B + 12"	F	9'-0"

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE
SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:
CUSTOMER ORDER NUMBER:
SOLD TO:
END USER:

QUANTITY OF DOORS:
DOOR MODEL NO: 160
DOOR ASSEMBLY NO: BPSL
ELECTRICAL DRAWING NO: 18D248

FEATURES

HEADER & RAIL: ■ ALUMINUM	OPERATION: ■ POWER DOOR – 115V, 1Ø
OPERATOR: ■ STANDARD DUTY	SHROUD: ■ SLOPED STAINLESS STEEL
DOOR PANEL MATERIAL: ■ WHITE LAMINATED FIBERGLASS	
CAPPING, SIDE FRAMES, SHROUD, WINDOW FRAME, & KICKPLATE MATERIAL (IF CHOSEN): ■ 304 #4 STAINLESS STEEL	
WINDOW TYPE: ■ NONE	GLASS TYPE: ■ NONE
OUTSIDE KICKPLATE: ■ NONE	INSIDE KICKPLATE: ■ NONE
KEYED CANEBOLT LOCK: ■ NONE	ELECTRIC LOCK: ■ NONE
PHOTO EYES: ■ (STD) DUAL SIDEFRAME @ 2" & 24"	INTERLOCKING: ■ NONE
BATTERY BACKUP: ■ NO	

ACTIVATION DEVICES

- (X042) () Wall Mount, Push Plate, 2-Gang (23A227)
(PIP1) () Push Plate Kit, In-Panel, 2-Gang (55B0033F07)
(X050) () Touchless Switch, 1 or 2 Gang Mount, Loose (23A288)
(PIP4) () Touchless Plate Kit, In-Panel, 2-Gang (55B0033F04)

SPECIAL NOTES

TAG DOOR AS: *****ADVISE*****

***** **ADVISE** *****

* DOOR TAG:

APPROVAL DRAWING



5848 North 95th Court
Milwaukee, WI 53225
1-800-558-7068
www.asidoors.com

TITLE
BI-PART SLIDE – POWER DOOR

DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.
----------	------	---------------	-------------	------