



FRAME/WALL/ANCHOR DETAIL

ADVISE



JAMB PROFILE, SLIDE-IN S/S FRAME





NOTE: WALL MUST BE REINFORCED. OPERATOR IS MOUNTED DIRECTLY TO WALL. 7GA PLATE, 8\"/>



FRAME/ANCHOR DETAIL

NOTE: IF INSWING OPERATOR NEEDED
SHROUD HEIGHT = B + 9 1/2\"/>

ADVISE



DOOR DIMENSIONS		
DOOR OPENING WIDTH	A	3'-0"
DOOR OPENING HEIGHT	B	7'-0"
FRAME HEIGHT (B + 2")	C	7'-2"
FRAME WIDTH (A + 4")	D	3'-4"
SHROUD HEIGHT (B + 8 1/8")	E	7'-8 1/8"

FEATURES

PANEL TYPE:

16GA. 304 #4 STAINLESS STEEL

FRAME MATERIAL:

16GA. 304 #4 STAINLESS STEEL

45' HOSPITAL STOP:

NONE

ANCHOR STYLE:

WELDED BACKBEND STRAP (BSA)

WINDOW TYPE: 304 #4 S/S FRAME

SINGLE PANE W/ SLOPED FRAME

KICKPLATE - PULL SIDE:

NONE

FRAME TYPE: WELDED

FLUSH W/ WALL, SINGLE RABBET

WALL CONSTRUCTION:

NEW STEEL STUD & DRYWALL

PANEL CAPPING:

NONE

GLASS TYPE:

CLEAR TEMPERED GLASS

KICK PLATE - PUSH SIDE:

NONE

POWER FEATURES

POWER OPERATOR:

T-TYPE - OUTSWING - 115 VAC, 1ø

OPERATOR SHROUD:

30', 304 #4 S/S, OUTSWING, FLUSH FRAME

ACTIVATION:

(X125) () Touchless Switch, MS11, Single Gang, Loose (23A0488)

STANDARD & LOOSE PARTS ITEMS

* PROVIDE

SPECIAL NOTES

TAG DOOR(S) AS: *****ADVISE*****

*****ADVISE*****

- * DOOR TAG:
- * SWING: RH (SHOWN) OR RHR OR LH OR LHR (USE HANDING DIAGRAM)
- * POWER HANDING:
- * WALL THICKNESS:
- * WALL CONSTRUCTION:
- * FRAME STYLE: WELDED (SHOWN) OR KNOCKDOWN
- * ANCHOR STYLE:
- * JAMB PROFILE: SLIDE IN/FLUSH (SHOWN) OR A WRAPPING WALL

APPROVAL DRAWING



5848 North 95th Court
Milwaukee, WI 53225
1-800-558-7068
www.asidoors.com

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE
SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:

CUSTOMER ORDER NUMBER:

SOLD TO:

END USER:

QUANTITY OF DOORS:

DOOR MODEL NO: 225SS

DOOR ASSEMBLY NO: SLSW

ELECTRICAL DRAWING NO: 18D292

TITLE

SINGLE SWING - POWERED DOOR

DRAWN BY

KS

DATE

SHEET
1 OF

DRAWING NO.

REV.