



FRAME/WALL/ANCHOR DETAIL

ADVISE



JAMB PROFILE, WRAPPING S/S FRAME



FEATURES

PANEL TYPE: U.L. FIRE RATED ■ 16GA. 304 #4 STAINLESS STEEL		FRAME TYPE: WELDED ■ WRAPPING WALL, SINGLE RABBET	
FRAME MATERIAL: U.L. FIRE RATED ■ 16GA. 304 #4 STAINLESS STEEL		WALL CONSTRUCTION: ■ NEW STEEL STUD & DRYWALL - FIRE RATED	
45° HOSPITAL STOP: ■ NONE		PANEL CAPPING: ■ NONE	
ANCHOR STYLE: U.L. FIRE RATED ■ NO MARK W/BASE (NMSSA-DR)		GLASS TYPE: U.L. FIRE RATED ■ FIRELITE PLUS	
WINDOW TYPE: 304 #4 S/S FRAME ■ SINGLE PANE W/ SLOPED FRAME		KICK PLATE - PULL SIDE: U.L. FIRE RATED ■ NONE	
KICKPLATE - PULL SIDE: U.L. FIRE RATED ■ NONE		KICK PLATE - PUSH SIDE: U.L. FIRE RATED ■ NONE	



STANDARD & LOOSE PARTS ITEMS

* PROVIDE

SPECIAL NOTES

TAG DOOR(S) AS: *****ADVISE*****

*** FEATURES & HARDWARE SUBJECT TO U.L. APPROVAL BEFORE MANUFACTURING MAY PROCEED ***



FRAME/ANCHOR DETAIL

DOOR DIMENSIONS

DOOR DIMENSION	LETTER	VALUE
DOOR OPENING WIDTH	A	3'-0"
DOOR OPENING HEIGHT	B	7'-0"
FRAME HEIGHT (B + 2")	C	7'-2"
FRAME WIDTH (A + 4")	D	3'-4"

******* ADVISE *******

- * DOOR TAG:
- * SWING: RH (SHOWN) OR RHR OR LH OR LHR (USE HANDING DIAGRAM)
- * WALL THICKNESS:
- * WALL CONSTRUCTION:
- * FRAME STYLE: WELDED (SHOWN) OR KNOCKDOWN
- * ANCHOR STYLE:
- * JAMB PROFILE: SLIDE IN/FLUSH (SHOWN) OR A WRAPPING WALL

APPROVAL DRAWING



5848 North 95th Court
Milwaukee, WI 53225
1-800-558-7068
www.asidoors.com

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:
CUSTOMER ORDER NUMBER:
SOLD TO:
END USER:

QUANTITY OF DOORS:
DOOR MODEL NO: 220SSFR
DOOR ASSEMBLY NO: SSWF
ELECTRICAL DRAWING NO:

TITLE
SINGLE SWING - MANUAL DOOR
90 MINUTE FIRE RATED PANEL

DRAWN BY KS	DATE	SHEET 1 OF	DRAWING NO.	REV.
----------------	------	---------------	-------------	------