



FRAME/WALL/ANCHOR DETAIL

ADVISE



JAMB PROFILE, WRAPPING S/S FRAME



NOTE: WALL MUST BE REINFORCED. OPERATOR IS MOUNTED DIRECTLY TO WALL. 7GA PLATE, 8" HIGH STARTING AT TOP OF ROUGH OPENING EXTENDING TO (1) STUD PAST EACH SIDE OF FRAME. (MIN. REQUIREMENT, BY CUSTOMER)



FRAME/ANCHOR DETAIL

NOTE: IF INSWING OPERATOR NEEDED SHROUD HEIGHT = B + 9 1/2"

ADVISE



DOOR DIMENSIONS		
DOOR OPENING WIDTH	A	6'-0"
DOOR OPENING HEIGHT	B	7'-0"
FRAME HEIGHT (B + 2")	C	7'-2"
FRAME WIDTH (A + 4")	D	6'-4"
SHROUD HEIGHT (B + 8 1/8")	E	7'-8 1/8"

FEATURES

PANEL TYPE: U.L. FIRE RATED ■ 16GA. 304 #4 STAINLESS STEEL	
FRAME MATERIAL: U.L. FIRE RATED ■ 16GA. 304 #4 STAINLESS STEEL	FRAME TYPE: WELDED ■ WRAPPING WALL, SINGLE RABBET
45' HOSPITAL STOP: ■ NONE	WALL CONSTRUCTION: ■ NEW STEEL STUD & DRYWALL - FIRE RATED
ANCHOR STYLE: U.L. FIRE RATED ■ NO MARK W/BASE (NMSSA-DR)	PANEL CAPPING: ■ NONE
WINDOW TYPE: 304 #4 S/S FRAME ■ SINGLE PANE W/ SLOPED FRAME	GLASS TYPE: U.L. FIRE RATED ■ FIRELITE PLUS
KICKPLATE - PULL SIDE: U.L. FIRE RATED ■ NONE	KICK PLATE - PUSH SIDE: U.L. FIRE RATED ■ NONE

POWER FEATURES

POWER OPERATOR: ■ T-TYPE - OUTSWING - 115 VAC, 1ø	OPERATOR SHROUD: ■ 30', 304 #4 S/S, OUTSWING, FLUSH FRAME
ACTIVATION: (X125) () Touchless Switch, MS11, Single Gang, Loose (23A0488)	

STANDARD & LOOSE PARTS ITEMS

* PROVIDE

SPECIAL NOTES

TAG DOOR(S) AS: *****ADVISE*****

*** FEATURES & HARDWARE SUBJECT TO U.L. APPROVAL BEFORE MANUFACTURING MAY PROCEED ***

*****ADVISE*****

- * DOOR TAG:
- * SWING: RH/LH (SHOWN) OR RHR/LHR (USE HANDING DIAGRAM)
- * POWER HANDING:
- * ACTIVE LEAF: RH OR LH OR BOTH (SHOWN) OR RHR OR LHR OR BOTH
- * WALL THICKNESS:
- * WALL CONSTRUCTION:
- * FRAME STYLE: WELDED (SHOWN) OR KNOCKDOWN
- * ANCHOR STYLE:
- * JAMB PROFILE: SLIDE IN/FLUSH (SHOWN) OR A WRAPPING WALL

APPROVAL DRAWING



5848 North 95th Court
Milwaukee, WI 53225
1-800-558-7068
www.asidoors.com

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:
CUSTOMER ORDER NUMBER:
SOLD TO:
END USER:

QUANTITY OF DOORS:
DOOR MODEL NO: 235SSFR
DOOR ASSEMBLY NO: PSWF
ELECTRICAL DRAWING NO: 18D293

TITLE PAIRED SWING - POWERED DOOR 90 MINUTE FIRE RATED PANEL				
DRAWN BY KS	DATE	SHEET 1 OF	DRAWING NO.	REV.