




**FRAME/WALL/ANCHOR DETAIL**

**ADVISE**



JAMB PROFILE, WRAPPING S/S FRAME



FEATURES	
PANEL TYPE: U.L. FIRE RATED ■ 16GA. 304 #4 STAINLESS STEEL	FRAME TYPE: WELDED ■ WRAPPING WALL, SINGLE RABBET
FRAME MATERIAL: U.L. FIRE RATED ■ 16GA. 304 #4 STAINLESS STEEL	WALL CONSTRUCTION: ■ NEW STEEL STUD & DRYWALL - FIRE RATED
45° HOSPITAL STOP: ■ NONE	PANEL CAPPING: ■ NONE
ANCHOR STYLE: U.L. FIRE RATED ■ NO MARK W/BASE (NMSSA-DR)	GLASS TYPE: U.L. FIRE RATED ■ FIRELITE PLUS
WINDOW TYPE: 304 #4 S/S FRAME ■ SINGLE PANE W/ SLOPED FRAME	KICK PLATE - PUSH SIDE: U.L. FIRE RATED ■ NONE
KICKPLATE - PULL SIDE: U.L. FIRE RATED ■ NONE	



**STANDARD & LOOSE PARTS ITEMS**

\* PROVIDE

**SPECIAL NOTES**

TAG DOOR(S) AS: **\*\*\*ADVISE\*\*\***

\*\*\* FEATURES & HARDWARE SUBJECT TO U.L. APPROVAL BEFORE MANUFACTURING MAY PROCEED \*\*\*



**FRAME/ANCHOR DETAIL**

DOOR DIMENSIONS		
DOOR OPENING WIDTH	A	6'-0"
DOOR OPENING HEIGHT	B	7'-0"
FRAME HEIGHT (B + 2")	C	7'-2"
FRAME WIDTH (A + 4")	D	6'-4"

**\*\*\*\*\*ADVISE\*\*\*\*\***

- \* DOOR TAG:
- \* SWING: RH/LH (SHOWN) OR RHR/LHR (USE HANDING DIAGRAM)
- \* ACTIVE LEAF: RH OR LH (SHOWN) OR BOTH OR RHR OR LHR OR BOTH
- \* WALL THICKNESS:
- \* WALL CONSTRUCTION:
- \* FRAME STYLE: WELDED (SHOWN) OR KNOCKDOWN
- \* ANCHOR STYLE:
- \* JAMB PROFILE: SLIDE IN/FLUSH (SHOWN) OR A WRAPPING WALL

**APPROVAL DRAWING**



5848 North 95th Court  
Milwaukee, WI 53225  
1-800-558-7068  
www.asidoors.com

**APPROVALS**

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY \_\_\_\_\_ DATE \_\_\_\_\_

ASI JOB NUMBER:  
CUSTOMER ORDER NUMBER:  
SOLD TO:  
END USER:

QUANTITY OF DOORS:  
DOOR MODEL NO: 230SSFR  
DOOR ASSEMBLY NO: PSWF  
ELECTRICAL DRAWING NO:

TITLE PAIRED SWING - MANUAL DOOR 90 MINUTE FIRE RATED PANEL				
DRAWN BY KS	DATE	SHEET 1 OF	DRAWING NO.	REV.