



DOOR DIMENSIONS		
FINISHED OPENING WIDTH	A	6'-0"
FINISHED OPENING HEIGHT	B	8'-0"
A/2 + 10 1/2"	C	3'-10 1/2"
A/2 + 18 1/2"	D	4'-6 1/2"
A/2 + 25"	E	5'-1"
A/2 + 12"	F	4'-0"
2A + 37"	G	15'-1"
B + 17"	H	9'-5"
B + 18 1/4"	I	9'-6 1/4"

NOTE:  
IF USING A JUNCTION BOX TO BRING POWER TO THE OPERATOR USING THE SUPPLIED HEADER CUTOUT, BOX MUST BE FLUSH WITH THE WALL AND WIRING MUST NOT INTERFERE WITH THE DOOR MOTION.

FEATURES	
HEADER & RAIL: <input checked="" type="checkbox"/> STAINLESS STEEL	OPERATION: <input checked="" type="checkbox"/> POWER DOOR - 115V, 1Ø
OPERATOR: <input checked="" type="checkbox"/> STANDARD DUTY	SHROUD: <input checked="" type="checkbox"/> 30' SLOPED STAINLESS STEEL
DOOR PANEL MATERIAL: <input checked="" type="checkbox"/> 304 #4 STAINLESS STEEL	
CAPPING, SIDE FRAMES, SHROUD, & WINDOW FRAME MATERIAL (IF CHOSEN): <input checked="" type="checkbox"/> 304 #4 STAINLESS STEEL	
WINDOW TYPE: <input checked="" type="checkbox"/> NONE	GLASS TYPE: <input checked="" type="checkbox"/> NONE
PHOTO EYES: <input checked="" type="checkbox"/> (STD) DUAL SIDEFAME @ 2" & 24"	ELECTRIC LOCK: <input checked="" type="checkbox"/> NONE
INTERLOCKING: <input checked="" type="checkbox"/> NONE	
ALTERNATE POWER SOURCE - REQUIRES ONE OF THE FOLLOWING: YES NO <input type="checkbox"/> BATTERY BACK-UP PROVIDED BY ASI DOORS <input type="checkbox"/> BACK-UP POWER SOURCE PROVIDED BY OTHERS	
FIRE SIGNAL - REQUIRES ONE OF THE FOLLOWING: YES NO <input type="checkbox"/> HEAT SENSOR PROVIDED BY ASI DOORS (23A0466) <input type="checkbox"/> FIRE ALARM SIGNAL PROVIDED BY OTHERS	
SMOKE DETECTOR - OPTIONAL SIGNAL: YES NO <input type="checkbox"/> SMOKE DETECTOR W/ ALARM/STROBE PROVIDED BY ASI DOORS (23A0452) <input type="checkbox"/> SMOKE DETECTOR PROVIDED BY OTHERS	

ACTIVATION DEVICES		
(X042)	( )	Wall Mount, Push Plate, 2-Gang, Loose (23A227)
(X047)	( )	3-Button Station, Open/Close/E-Stop, Loose (24A001)
(X050)	( )	Touchless Switch, 1 or 2 Gang Mount, Loose (23A288)
(X027)	( )	Motion Sensor ASI-Falc, Loose (23A284)
(X100)	( )	Pull Cord, Unheated, Loose (24C507F1)
(X125)	( )	Touchless Switch, MS11, Single Gang, Loose (23A0488)

SPECIAL NOTES  
TAG DOOR AS: **\*\*\*ADVISE\*\*\***

**\*\*\*\*\* ADVISE \*\*\*\*\***  
\* DOOR TAG:  
\* OPERATOR LOCATION: RH SIDE (SHOWN), LH SIDE IS OPPOSITE

**APPROVAL DRAWING**

**ASIDOORS** 5848 North 95th Court  
Milwaukee, WI 53225  
1-800-558-7068  
www.asidoors.com

TITLE BI-PART SLIDE FIRE DOOR - POWERED 90 MINUTE RATING				
DRAWN BY KS	DATE	SHEET 1 OF	DRAWING NO.	REV.

APPROVALS  
FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.  
BY \_\_\_\_\_ DATE \_\_\_\_\_

ASI JOB NUMBER:  
CUSTOMER ORDER NUMBER:  
SOLD TO:  
END USER:

QUANTITY OF DOORS: 1  
DOOR MODEL NO: 265SSFR  
DOOR ASSEMBLY NO: BPSF  
ELECTRICAL DRAWING NO: 18D340