



ADVISE

FEATURES

VOLTAGE:
☐ 115V 1ø 60HZ ** ☐ 208V 1ø 60HZ ☐ 230 1ø 60HZ ☐ 460 3ø 60 HZ

CURTAIN COLOR:
☐ BLUE ☐ ORANGE ☐ OTHER _____

VISION:
☒ STANDARD FULL WIDTH (28"xFULL WIDTH)

CONSTRUCTION MATERIAL:
☒ STD. GALVANIZED STEEL - ANGLE & PLATE

SHROUD:
☒ FLAT SHROUD ASSEMBLY

SIDE GUIDE COVERS:
☒ YES ☐ NO

SHROUD & SIDE GUIDE COVER MATERIAL:
☒ STANDARD GALVANIZED STEEL

PHOTO-EYE:
☒ STANDARD SINGLE

INTERLOCK PREP: (# OF DOORS ____)
☐ YES ☒ NO

BATTERY BACKUP SYSTEM: (ONLY ON 115V UNITS)
☐ YES ☒ NO

DOOR CLOSED STATUS CONTACTS:
☐ YES ☒ NO

DOOR OPEN STATUS CONTACTS:
☐ YES ☒ NO

CONTROL PANEL:
☒ STANDARD POLYCARBONATE

EXTENDED CABLES: LENGTH = ____ (50' MAX)
☐ YES ☒ NO

PRE-ANNOUNCE TO CLOSE: (# OF STACKS ____)
☐ YES ☒ NO

SELECT COMPONENTS (PER STACK) MAX OF 1 ALARM PER STACK
ALARM MULTI-TONE: QTY. ____ (23A0459-1)
LIGHTS: RED QTY. ____ (23A0458-1), YELLOW QTY. ____ (23A0458-2), GREEN QTY. ____ (23A0458-3)

ACTIVATION DEVICES

- (X042) () Wall Mount, Push Plate, 2-Gang, Loose (23A227)
(X106) () Wall Plate, Single Gang, S/S, Flush, Loose (24A0083NN20)
(X107) () Wall Plate, 2-Gang, S/S, Flush, Loose (24A0084NN20)
(X125) () Touchless Switch, MS11, Single Gang, Loose (23A0488)
(X100) () Pull Cord, Unheated, Loose (24C507F1)
(X101) () Pull Cord, Heated, Loose (24C507F2)
(X045) () Single Button Station, Unheated, Loose (24B029F1)
(X046) () Single Button Station, Heated, Loose (24B029F2)

SPECIAL NOTES

TAG DOOR(S) AS: *****ADVISE*****

***** ADVISE *****

- * DOOR TAG:
* CURTAIN COLOR: BLUE OR ORANGE
* OPERATOR LOCATION: RIGHT HAND (SHOWN), LEFT IS OPPOSITE
* VOLTAGE: 115, 208, OR 230 SINGLE PHASE OR 460 VOLTS, 3 PHASE

APPROVAL DRAWING



5848 North 95th Court
Milwaukee, WI 53225
1-800-558-7068
www.asidoors.com

TITLE
HIGH SPEED FABRIC ROLL-UP
RIGHT HAND OPERATOR

DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.
----------	------	---------------	-------------	------

DOOR DIMENSIONS

FINISHED OPENING WIDTH	A	8'-0"
FINISHED OPENING HEIGHT	B	10'-0"
A + 5 1/2"	C	8'-5 1/2"
A + 14"	D	9'-2"
B + 18"	E	11'-6"

NOTE: 1/2" SHROUD REMOVAL CLEARANCE

MOTOR DATA
1 HP or 2 HP

VOLT/PHASE	RECOMMENDED SERVICE
460/3	6 AMPS
230/1	15 AMPS
208/1	15 AMPS
115/1 **	20 AMPS

NOTE: 208 & 230 VAC CONTROLS
ARE SET TO WORK WITH EITHER
SINGLE PHASE OR 3 PHASE
POWER INPUT.

** 115 VAC OPTION ONLY AVAILABLE ON DOORS 140 SQ FT OR LESS

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE
SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:
CUSTOMER ORDER NUMBER:
SOLD TO:
END USER:

QUANTITY OF DOORS:
DOOR MODEL NO: 515
DOOR ASSEMBLY NO: 91B0008
ELECTRICAL DRAWING NO: