



FEATURES

VOLTAGE:
☐ 208V 1ø 60HZ ☐ 230 1ø 60HZ ☐ 460 3ø 60 HZ (REQUIRES DEDICATED NEUTRAL FOR HEAT)

CURTAIN COLOR:
☐ BLUE ☐ ORANGE ☐ OTHER _____

CURTAIN OPTIONS:
☒ STANDARD NON-INSULATED

MOTOR & BELT COVERS:
☒ YES ☐ NO

CONTROL PANEL:
☒ STD GRAY PAINTED FINISH

PHOTO-EYE:
☒ STANDARD SINGLE

DOOR CLOSED STATUS CONTACTS:
☐ YES ☒ NO

BLOWER UNIT:
☐ YES ☒ NO

PRE-ANNOUNCE TO CLOSE: (# OF STACKS _____)
☐ YES ☒ NO
SELECT COMPONENTS (PER STACK) MAX OF 1 ALARM PER STACK
ALARM MULTI-TONE: QTY. _____ (23A0459-1)
LIGHTS: RED QTY. _____ (23A0458-1), YELLOW QTY. _____ (23A0458-2), GREEN QTY. _____ (23A0458-3)

CONSTRUCTION MATERIAL:
☒ STANDARD GALVANIZED STEEL

DRUM FASCIA (SHROUD W/ OPEN TOP):
☒ YES ☐ NO

EXTENDED CABLES: LENGTH = _____ (50' MAX)
☐ YES ☒ NO

INTERLOCK PREP: (# OF DOORS _____)
☐ YES ☒ NO

DOOR OPEN STATUS CONTACTS:
☐ YES ☒ NO

ACTIVATION DEVICES

(X100) () Pull Cord, Unheated, Loose (24C507F1)

(X101) () Pull Cord, Heated, Loose (24C507F2)

(X045) () Single Button Station, Unheated, Loose (24B029F1)

(X046) () Single Button Station, Heated, Loose (24B029F2)

SPECIAL NOTES

TAG DOOR(S) AS: *****ADVISE*****

***** ADVISE *****

* MOUNT SIDE TEMP: _____.

* OPPOSITE SIDE TEMP: _____.

***** ADVISE *****

* DOOR TAG:

* CURTAIN COLOR: BLUE OR ORANGE

* OPERATOR LOCATION: RIGHT HAND (SHOWN), LEFT IS OPPOSITE

* VOLTAGE: 208V, OR 230V SINGLE PHASE OR 460V 3 PHASE

APPROVAL DRAWING

ASIDOORS

5848 North 95th Court
Milwaukee, WI 53225
1-800-558-7068
www.asidoors.com

TITLE
HIGH SPEED FABRIC ROLL-UP
RIGHT HAND OPERATOR – FREEZER

DRAWN BY

DATE

SHEET
1 OF

DRAWING NO.

REV.

MOTOR DATA 2 HP (1.5 KW)	
VOLT/PHASE	RECOMMENDED SERVICE
460/3	15 AMPS
230/1	20 AMPS
208/1	20 AMPS

NOTE: 460 VAC UNITS REQUIRE 277 VAC FOR SIDE FRAME HEAT. A DEDICATED NEUTRAL WILL BE REQUIRED

NOTE: 208 & 230 VAC CONTROLS ARE SET TO WORK WITH EITHER SINGLE PHASE OR 3 PHASE POWER INPUT.

NOTE: SIDE FRAME HEAT TAPE REQUIRES A DEDICATED NEUTRAL FOR PROPER OPERATION OR A SEPARATE HEAT TAPE TRANSFORMER (DOES NOT REQUIRE DEDICATED NEUTRAL)

DOOR DIMENSIONS			
FINISHED OPENING WIDTH	A	8'-0"	
FINISHED OPENING HEIGHT	B	10'-0"	
A + 11"	C	8'-11"	
A + 19"	D	9'-7"	
B + "F"	E		

NOTE: 1/2" SHROUD REMOVAL CLEARANCE

NOTE: HEATED CONTROL PANEL REQUIRED IF PANEL IS MOUNTED IN AN AREA BELOW 32°F		
	SHROUD HEIGHT CLEAR = "F"	SHROUD PROJECTION CLEAR = "G"
FOH≤16'0"	25 3/4"	22"
FOH>16'0"	28"	25"

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:

CUSTOMER ORDER NUMBER:

SOLD TO:

END USER:

QUANTITY OF DOORS:

DOOR MODEL NO: 615F

DOOR ASSEMBLY NO: 91B0009

ELECTRICAL DRAWING NO: