



FEATURES	
VOLTAGE: <input type="checkbox"/> 208V 1ø 60HZ <input type="checkbox"/> 230 1ø 60HZ <input type="checkbox"/> 460 3ø 60 HZ (REQUIRES DEDICATED NEUTRAL FOR HEAT)	
CURTAIN COLOR: <input type="checkbox"/> BLUE <input type="checkbox"/> ORANGE <input type="checkbox"/> OTHER _____	
CURTAIN OPTIONS: <input checked="" type="checkbox"/> INSULATED	CONSTRUCTION MATERIAL: <input checked="" type="checkbox"/> STANDARD GALVANIZED STEEL
MOTOR & BELT COVERS: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	DRUM FASCIA (SHROUD W/ OPEN TOP): <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
CONTROL PANEL: <input checked="" type="checkbox"/> STD GRAY PAINTED FINISH	EXTENDED CABLES: LENGTH = ____ (50' MAX) <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
PHOTO-EYE: <input checked="" type="checkbox"/> STANDARD SINGLE	INTERLOCK PREP: (# OF DOORS ____) <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
DOOR CLOSED STATUS CONTACTS: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	DOOR OPEN STATUS CONTACTS: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
BLOWER UNIT: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
PRE-ANNOUNCE TO CLOSE: (# OF STACKS ____) <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
SELECT COMPONENTS (PER STACK) MAX OF 1 ALARM PER STACK ALARM MULTI-TONE: QTY. ____ (23A0459-1) LIGHTS: RED QTY. ____ (23A0458-1), YELLOW QTY. ____ (23A0458-2), GREEN QTY. ____ (23A0458-3)	

ACTIVATION DEVICES	
(X100)	( ) Pull Cord, Unheated, Loose (24C507F1)
(X101)	( ) Pull Cord, Heated, Loose (24C507F2)
(X045)	( ) Single Button Station, Unheated, Loose (24B029F1)
(X046)	( ) Single Button Station, Heated, Loose (24B029F2)

SPECIAL NOTES	
TAG DOOR(S) AS: <b>***ADVISE***</b>	
<div>***** <b>ADVISE</b> ***** * MOUNT SIDE TEMP: _____ : * OPPOSITE SIDE TEMP: _____ :</div>	

<div>***** <b>ADVISE</b> ***** * DOOR TAG: * CURTAIN COLOR: BLUE OR ORANGE * OPERATOR LOCATION: RIGHT HAND (SHOWN), LEFT IS OPPOSITE * VOLTAGE: 208V, OR 230V SINGLE PHASE OR 460V 3 PHASE</div>
--

APPROVAL DRAWING

5848 North 95th Court  
Milwaukee, WI 53225  
1-800-558-7068  
www.asidoors.com

TITLE HIGH SPEED FABRIC ROLL-UP RIGHT HAND OPERATOR – FREEZER				
DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.

MOTOR DATA 2 HP (1.5 KW)	
VOLT/PHASE	RECOMMENDED SERVICE
460/3	15 AMPS
230/1	20 AMPS
208/1	20 AMPS

NOTE: 460 VAC UNITS REQUIRE 277 VAC FOR SIDE FRAME HEAT. A DEDICATED NEUTRAL WILL BE REQUIRED

NOTE: 208 & 230 VAC CONTROLS ARE SET TO WORK WITH EITHER SINGLE PHASE OR 3 PHASE POWER INPUT.

NOTE: SIDE FRAME HEAT TAPE REQUIRES A DEDICATED NEUTRAL FOR PROPER OPERATION OR A SEPARATE HEAT TAPE TRANSFORMER (DOES NOT REQUIRE DEDICATED NEUTRAL)

DOOR DIMENSIONS			
FINISHED OPENING WIDTH	A	8'-0"	
FINISHED OPENING HEIGHT	B	10'-0"	
A + 11"	C	8'-11"	
A + 16 1/4"	D	9'-4 1/4"	
B + 25"	E	12'-1"	

NOTE: HEATED CONTROL PANEL REQUIRED IF PANEL IS MOUNTED IN AN AREA BELOW 32°F

APPROVALS	
FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.	
BY _____	DATE _____

ASI JOB NUMBER:
CUSTOMER ORDER NUMBER:
SOLD TO:
END USER:

QUANTITY OF DOORS:
DOOR MODEL NO:            615F
DOOR ASSEMBLY NO:        91B0009
ELECTRICAL DRAWING NO: