


FEATURES	
VOLTAGE: <input type="checkbox"/> 208V 1ø 60HZ <input type="checkbox"/> 230 1ø 60HZ <input type="checkbox"/> 460 3ø 60 HZ (REQUIRES DEDICATED NEUTRAL FOR HEAT)	
CURTAIN COLOR: <input type="checkbox"/> BLUE <input type="checkbox"/> ORANGE <input type="checkbox"/> OTHER _____	
CURTAIN OPTIONS: <input checked="" type="checkbox"/> STANDARD NON-INSULATED	CONSTRUCTION MATERIAL: <input checked="" type="checkbox"/> STANDARD GALVANIZED STEEL
MOTOR & BELT COVERS: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	DRUM FASCIA (SHROUD W/ OPEN TOP): <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
CONTROL PANEL: <input checked="" type="checkbox"/> STD GRAY PAINTED FINISH	EXTENDED CABLES: LENGTH = ____ (50' MAX) <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
PHOTO-EYE: <input checked="" type="checkbox"/> STANDARD SINGLE	INTERLOCK PREP: (# OF DOORS ____) <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
DOOR CLOSED STATUS CONTACTS: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	DOOR OPEN STATUS CONTACTS: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
BLOWER UNIT: <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
PRE-ANNOUNCE TO CLOSE: (# OF STACKS ____) <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
SELECT COMPONENTS (PER STACK) MAX OF 1 ALARM PER STACK ALARM MULTI-TONE: QTY. ____ (23A0459-1) LIGHTS: RED QTY. ____ (23A0458-1), YELLOW QTY. ____ (23A0458-2), GREEN QTY. ____ (23A0458-3)	

ACTIVATION DEVICES	
(X100)	() Pull Cord, Unheated, Loose (24C507F1)
(X101)	() Pull Cord, Heated, Loose (24C507F2)
(X045)	() Single Button Station, Unheated, Loose (24B029F1)
(X046)	() Single Button Station, Heated, Loose (24B029F2)

SPECIAL NOTES	
TAG DOOR(S) AS: ***ADVISE***	
<div>***** ADVISE *****</div> <div>* MOUNT SIDE TEMP: _____.</div> <div>* OPPOSITE SIDE TEMP: _____.</div>	

<div>***** ADVISE *****</div> <div>* DOOR TAG:</div> <div>* CURTAIN COLOR: BLUE OR ORANGE</div> <div>* OPERATOR LOCATION: RIGHT HAND (SHOWN), LEFT IS OPPOSITE</div> <div>* VOLTAGE: 208V, OR 230V SINGLE PHASE OR 460V 3 PHASE</div>
--

APPROVAL DRAWING



5848 North 95th Court
Milwaukee, WI 53225
1-800-558-7068
www.asidoors.com

TITLE HIGH SPEED FABRIC ROLL-UP RIGHT HAND OPERATOR – FREEZER				
DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.

MOTOR DATA 2 HP (1.5 KW)	
VOLT/PHASE	RECOMMENDED SERVICE
460/3	15 AMPS
230/1	20 AMPS
208/1	20 AMPS

NOTE: 460 VAC UNITS REQUIRE 277 VAC FOR SIDE FRAME HEAT. A DEDICATED NEUTRAL WILL BE REQUIRED

NOTE: 208 & 230 VAC CONTROLS ARE SET TO WORK WITH EITHER SINGLE PHASE OR 3 PHASE POWER INPUT.

NOTE: SIDE FRAME HEAT TAPE REQUIRES A DEDICATED NEUTRAL FOR PROPER OPERATION OR A SEPARATE HEAT TAPE TRANSFORMER (DOES NOT REQUIRE DEDICATED NEUTRAL)

DOOR DIMENSIONS			
FINISHED OPENING WIDTH	A	8'-0"	
FINISHED OPENING HEIGHT	B	10'-0"	
A + 11"	C	8'-11"	
A + 16 1/4"	D	9'-4 1/4"	
B + 25"	E	12'-1"	

NOTE: HEATED CONTROL PANEL REQUIRED IF PANEL IS MOUNTED IN AN AREA BELOW 32°F

APPROVALS	
FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.	
BY _____	DATE _____

ASI JOB NUMBER:
CUSTOMER ORDER NUMBER:
SOLD TO:
END USER:

QUANTITY OF DOORS:
DOOR MODEL NO: 615F
DOOR ASSEMBLY NO: 91B0009
ELECTRICAL DRAWING NO: