



FOR OFFICE USE ONLY
 B-WIC
 B-HIC



BLOWER POWER (5 HP)
 480 VOLTS, 3 PH, 60 Hz
 3 CONDUCTORS PLUS GROUND



FEATURES

- VOLTAGE:**
 480V, 3 ϕ (STD)
- MATERIAL CONSTRUCTION:**
 STAINLESS STEEL GALVANIZED
- MOUNT:**
 FREEZER (INSULATED) COOLER (NON-INSULATED)
- AIR SUPPLY:**
 LEFT HAND RIGHT HAND
- HIC:**
 HIC \leq 132" HIC > 132"

DOOR DIMENSIONS

WIDTH IN CLEAR (WIC)	A	8'-0"
HEIGHT IN CLEAR (HIC)	B	12'-0"
A + 70"	C	13'-10"
B + 46"	D	15'-10"

DOOR #A SINGLE ELECTRIC

ELECTRICAL REQUIREMENTS (EACH PANEL)
 ELECTRICAL SCHEMATIC DOOR #A: 18D230
 * AIR SEAL - 5 HP 8.6 FLA
 * CONTROL BOX - 2.0 FLA
 * HEATER - 45.2 FLA (36 KW) EACH
 PANEL AMP DRAW = 56 @ 480 VAC

ELECTRICAL REQUIREMENTS (TOTAL)
 TOTAL FULL LOAD AMP DRAW = 115 @ 480 VAC
 DOOR HEAT AMP DRAW = 15 @ 115 VAC

SPECIAL NOTES

TAG DOOR AS: *****ADVISE*****

******* ADVISE *******

* DOOR TAG:
 * AIR SUPPLY: LEFT OR RIGHT (SHOWN)
 * DOCK SIDE TEMPERATURE: _____
 * FREEZER SIDE TEMPERATURE: _____

APPROVAL DRAWING



5848 North 95th Court
 Milwaukee, WI 53225
 1-800-558-7068
 www.asidoors.com

APPROVALS
 FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:
 CUSTOMER ORDER NUMBER:
 SOLD TO:
 END USER:

QUANTITY OF DOORS:
 DOOR MODEL NO: 715
 DOOR ASSEMBLY NO: 90D702F1
 ELECTRICAL DRAWING NO: SEE ABOVE

TITLE SINGLE AIRSEAL DOOR WITH SINGLE ELECTRIC HEAT

DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.
----------	------	------------	-------------	------