

ADVISE

FEATURES

VOLTAGE:  
☐ 230 3ø 60HZ    ☐ 460 3ø 60 HZ

VISION SLATS: (QTY. \_\_\_\_ )  
☒ NONE

BARREL & OPERATOR SHROUD:  
☒ YES

EXTENDED CABLE PACKAGE:  
☒ NO

REVERSING EDGE:  
☒ STD WIRELESS REVERSING EDGE (23B155)

REVERSING DEVICE:  
☒ STD DUAL PHOTO EYES

PRE-ANNOUNCE TO CLOSE:  
☒ NO

ACTIVATION DEVICES

- (X000) ( ) Loop Detector (only)
- (X000) ( ) Loop Detector, W/ Wire & Sealant
- (X027) ( ) Motion Sensor ASI/F (23A284)
- (X080) ( ) Motion Sensor Program Remote ASI/B, Loose (23A285)
- (X181) ( ) Radio Control, 1-Channel Receiver (23A0510)
- (X182) ( ) Radio Control, 1-Channel Transmitter W/Clip (23A0511)
- (X184) ( ) Radio Control, 2-Channel Transmitter W/Clip (23A0512)
- (X100) ( ) Pull Cord, Unheated (24C507F1)
- (X045) ( ) Single Button Station, Unheated (24B029F1)
- (X047) ( ) 3-Button Station, Open/Close/E-Stop (24A001)
- (X048) ( ) 3-Button Station, Open/Close/E-Stop W/Key (23A245)


SPECIAL NOTES

TAG DOOR(S) AS: **\*\*\*ADVISE\*\*\***

NOTE: FLOOR LEVELNESS & FLATNESS TO BE WITHIN 3/8" OVER WIDTH IN CLEAR FOR PROPER SEAL

DOOR DIMENSIONS

FINISHED OPENING WIDTH	A	12'-0"
FINISHED OPENING HEIGHT	B	12'-0"
B + 28"	C	14'-4"
A + 21"	D	13'-9"
A + 22 1/4"	E	13'-10 1/4"
B + 28 1/2"	F	14'-4 1/2"



MOTOR DATA 3.25 HP (2.5 KW)	
VOLT/PHASE	FLA
460/3	7.5 AMPS
230/3	12.5 AMPS

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY \_\_\_\_\_ DATE \_\_\_\_\_

ASI JOB NUMBER:  
CUSTOMER ORDER NUMBER:  
SOLD TO:  
END USER:

QUANTITY OF DOORS:  
DOOR MODEL NO: 209-D  
DOOR ASSEMBLY NO: 91B0018  
ELECTRICAL DRAWING NO:

\*\*\*\*\* **ADVISE** \*\*\*\*\*

\* DOOR TAG:  
\* OPERATOR LOCATION: RIGHT HAND (SHOWN), LEFT IS OPPOSITE  
\* VOLTAGE: 230 OR 460 VOLTS, 3 PHASE

APPROVAL DRAWING



5848 North 95th Court  
Milwaukee, WI 53225  
1-800-558-7068  
www.asidoors.com

TITLE  
APEX DURA ALUMINUM ROLLUP DOOR,  
RIGHT HAND DRIVE

DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.
----------	------	---------------	-------------	------