

ADVISE

FEATURES

- VOLTAGE:
☐ 230 3ø 60HZ ☐ 460 3ø 60 HZ
- VISION SLATS: (QTY. -)
☒ POLYCARBONATE - FULL WIDTH
- BARREL & OPERATOR SHROUD:
☒ YES
- EXTENDED CABLE PACKAGE:
☒ NO
- REVERSING EDGE:
☒ STD WIRELESS REVERSING EDGE (23B155)
- REVERSING DEVICE:
☒ STD DUAL PHOTO EYES
- PRE-ANNOUNCE TO CLOSE:
☒ NO

ACTIVATION DEVICES

- (X000) () Loop Detector (only)
(X000) () Loop Detector, W/ Wire & Sealant
(X027) () Motion Sensor ASI/F (23A284)
(X080) () Motion Sensor Program Remote ASI/B, Loose (23A285)
(X181) () Radio Control, 1-Channel Receiver (23A0510)
(X182) () Radio Control, 1-Channel Transmitter W/Clip (23A0511)
(X184) () Radio Control, 2-Channel Transmitter W/Clip (23A0512)
(X100) () Pull Cord, Unheated (24C507F1)
(X045) () Single Button Station, Unheated (24B029F1)
(X047) () 3-Button Station, Open/Close/E-Stop (24A001)
(X048) () 3-Button Station, Open/Close/E-Stop W/Key (23A245)

SPECIAL NOTES


TAG DOOR(S) AS: *****ADVISE*****

NOTE: FLOOR LEVELNESS & FLATNESS TO BE WITHIN 3/8" OVER WIDTH IN CLEAR FOR PROPER SEAL

DOOR DIMENSIONS

FINISHED OPENING WIDTH	A	12'-0"
FINISHED OPENING HEIGHT	B	12'-0"
B + 28"	C	14'-4"
A + 21"	D	13'-9"
A + 22 1/4"	E	13'-10 1/4"
B + 28 1/2"	F	14'-4 1/2"

SIDE FRAME DETAIL:



***** ADVISE *****

- * DOOR TAG:
* OPERATOR LOCATION: RIGHT HAND (SHOWN), LEFT IS OPPOSITE
* VOLTAGE: 230 OR 460 VOLTS, 3 PHASE

APPROVAL DRAWING



5848 North 95th Court
Milwaukee, WI 53225
1-800-558-7068
www.asidoors.com

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:
CUSTOMER ORDER NUMBER:
SOLD TO:
END USER:

QUANTITY OF DOORS:
DOOR MODEL NO: 209-V
DOOR ASSEMBLY NO: 91B0018
ELECTRICAL DRAWING NO:

TITLE
APEX VISION ALUMINUM ROLLUP DOOR,
RIGHT HAND DRIVE

DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.
----------	------	---------------	-------------	------