

ADVISE

FEATURES

- VOLTAGE:
☐ 230 3ø 60HZ ☐ 460 3ø 60 HZ
- VISION SLATS: (QTY. 4)
☒ POLYCARBONATE – FULL WIDTH
- BARREL & OPERATOR SHROUD:
☒ NO
- EXTENDED CABLE PACKAGE:
☒ NO
- REVERSING EDGE:
☒ STD WIRELESS REVERSING EDGE (23B155)
- REVERSING DEVICE:
☒ STD DUAL PHOTO EYES
- PRE-ANNOUNCE TO CLOSE:
☒ NO

ACTIVATION DEVICES

- (X000) () Loop Detector (only)
- (X000) () Loop Detector, W/ Wire & Sealant
- (X027) () Motion Sensor ASI/F (23A284)
- (X080) () Motion Sensor Program Remote ASI/B, Loose (23A285)
- (X181) () Radio Control, 1–Channel Receiver (23A0510)
- (X182) () Radio Control, 1–Channel Transmitter W/Clip (23A0511)
- (X184) () Radio Control, 2–Channel Transmitter W/Clip (23A0512)
- (X100) () Pull Cord, Unheated (24C507F1)
- (X045) () Single Button Station, Unheated (24B029F1)
- (X047) () 3–Button Station, Open/Close/E–Stop (24A001)
- (X048) () 3–Button Station, Open/Close/E–Stop W/Key (23A245)

SPECIAL NOTES

TAG DOOR(S) AS: *****ADVISE*****

NOTE: FLOOR LEVELNESS & FLATNESS TO BE WITHIN 3/8" OVER WIDTH IN CLEAR FOR PROPER SEAL


DOOR DIMENSIONS

FINISHED OPENING WIDTH	A	12'–0"
FINISHED OPENING HEIGHT	B	12'–0"
B + 28"	C	14'–4"
A + 21"	D	13'–9"

MOTOR DATA 3.25 HP (2.5 KW)

VOLT/PHASE	FLA
460/3	7.5 AMPS
230/3	12.5 AMPS

SIDE FRAME DETAIL:



***** **ADVISE** *****

- * DOOR TAG:
- * OPERATOR LOCATION: RIGHT HAND (SHOWN), LEFT IS OPPOSITE
- * VOLTAGE: 230 OR 460 VOLTS, 3 PHASE

APPROVAL DRAWING



5848 North 95th Court
Milwaukee, WI 53225
1–800–558–7068
www.asidoors.com

APPROVALS

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED.

BY _____ DATE _____

ASI JOB NUMBER:
CUSTOMER ORDER NUMBER:
SOLD TO:
END USER:

QUANTITY OF DOORS:
DOOR MODEL NO: 209–D
DOOR ASSEMBLY NO: 91B0018
ELECTRICAL DRAWING NO:

TITLE
APEX DURA ALUMINUM ROLLUP DOOR,
RIGHT HAND DRIVE

DRAWN BY	DATE	SHEET 1 OF	DRAWING NO.	REV.
----------	------	---------------	-------------	------